



# KENWORTH REPLACEMENT GAUGES



## High-Quality O.E.M. Replacements from Stewart Warner

### FEATURES:

- Direct O.E.M. replacements for Kenworth (KENMEX) Ametek-Dixson brand gauges.
- Six (6) standard mechanical gauges with tubing and four (4) electrical gauges.
- Three (3) temperature senders.
- Easy installation via mounting stud.
- High-quality Stewart Warner brand instruments that look as good as they perform!
- Black bezels with silver trim ring--just like the originals.
- Black pointer hub with bright red pointer.
- Black dial with white-on-black graphics; metric scale; color coded voltmeter.
- Superior high-temperature & thermal shock resistance.
- Rugged metal cases.
- Color-keyed temperature senders (black, red and white ID ring).

### CROSS-REFERENCES:

DESCRIPTION	SW P/N	AD P/N	KW P/N	SENDER
<b>MECHANICAL GAUGES</b>				
Air pressure gauge, 70-1000 kPa, 2-1/16" (52 mm), mechanical.	490ADF	147786	K-152-C-321	-
Oil pressure gauge, 50-700 kPa, 2-1/16" (52 mm), mechanical.	490ADH	147785	K-152-322	-
Water temperature gauge, 40-130°C, 2-1/16" (52 mm), with 72" capillary tube, mechanical.	491HC72	-	K-152-151-1	-
Water temperature gauge, 40-130°C, 2-1/16" (52 mm), with 96" capillary tube, mechanical.	491HC96	-	K-152-166-1	-
Transmission oil temperature gauge, 60-160°C, 2-1/16" (52 mm), with 72" capillary tube, mechanical.	491HB72	-	-	-
Transmission oil temperature gauge, 60-160°C, 2-1/16" (52 mm), with 96" capillary tube, mechanical.	491HB96	-	-	-
<b>ELECTRICAL GAUGES</b>				
Voltmeter, 10-16 VDC, red-yellow-green color-coding, 2-1/16" (52 mm), electrical.	474CZ	144736	K-152-304	-
Water temperature gauge, 40-115°C, 2-1/16" (52 mm), electrical	467KF	147781	K-152-327	334FA
Transmission oil temperature gauge, 60-160°C, 2-1/16" (52 mm), electrical.	467KE	152840	K-152-150	334FC
Fuel gauge, E-1/2-F, SW match, 2-1/16" (52 mm), electrical	457CX	144735	K-152-305	-
<b>TEMPERATURE SENDERS</b>				
Differential temperature sender, 60-160°C, 1/2" NPTF, black.	334FB	-	-	-
Transmission oil temperature sender, 60-160°C, 1/2" NPTF, red.	334FC	-	-	-
Water temperature sender, 40-110°C, 1/2" NPTF, white.	334FA	-	-	-
<b>REPLACEMENT BULB</b>				
12 VDC, G-4-1/2 min, bay, 2-CP, GE #57.	825810	-	-	-



490ADF



490ADH



491HC72/96



491HB72/96



474CZ



334FA

334FC

334FB



467KF



467KE



MOUNTING STUD ENSURES EASY INSTALLATION